

## Section 1 - Identification of The Material and Supplier

**Howard Products (Aust)**  
**33 Griffin Avenue**  
**Tamworth, NSW 2340**

Phone: 1800 672 646 (business hours)  
0419 403 627 or 0427 403 627 (after hours)  
Fax: 02 6766 9933  
info@howardproducts.com.au

**Chemical nature:** Blend of solvents.  
**Trade Name:** **Restor-A-Finish**  
**Product Use:** Wood finish restorer.  
**Creation Date:** **July, 2012**  
**This version issued:** **June, 2021** and is valid for 5 years from this date.  
**Poisons Information Centre: Phone 13 1126 from anywhere in Australia**

## Section 2 - Hazards Identification

### Statement of Hazardous Nature

This product is classified as: Xn, Harmful. F+, Highly Flammable. Not classified as hazardous according to the criteria of SWA.

Dangerous according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria.

**SUSMP Classification:** None allocated.

**ADG Classification:** Class 3: Flammable liquids.

**UN Number:** 1263, PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound) (see 3.2.5 for relevant AUST entries)



### GHS Signal word: DANGER

Flammable liquid category 2  
Aspiration hazard category 1  
Serious eye irritation category 2A  
Specific target organ toxicity (single exposure) category 3

#### HAZARD

H225: Highly flammable liquid and vapour.  
AUH066: Repeated exposure may cause skin dryness or cracking  
H305: May be harmful if swallowed and enters airways.  
H319: Causes serious eye irritation.  
H336: May cause drowsiness or dizziness.

#### PREVENTION

P210: Keep away from heat, sparks, open flames and hot surfaces. - No smoking.  
P223: Keep away from any possible contact with water, because of violent reaction and possible flash fire.  
P233: Keep container tightly closed.  
P240: Ground/bond container and receiving equipment.  
P241: Use explosion-proof electrical ventilating, lighting and other equipment.  
P242: Use only non-sparking tools.  
P243: Take precautionary measures against static discharge.  
P261: Avoid breathing fumes, mists and vapours.  
P271: Use only outdoors or in a well ventilated area.  
P280: Wear protective gloves, protective clothing and eye or face protection.

#### RESPONSE

P302: If on skin: remove contaminated clothing and flush skin with running water.  
P301+P312: IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell.  
P303+P361+P353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin and hair with water.  
P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P370+P378: In case of fire: Use carbon dioxide, dry chemical or foam for extinction.

#### STORAGE

P403+P235: Store in a well-ventilated place. Keep cool.

## SAFETY DATA SHEET

Issued by: Howard Products (Aust)

Phone: 1800 672 646 (business hours)

**Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)**

## DISPOSAL

P501: Dispose of contents to controlled incineration and containers to landfill. Do not discharge to waterways.

## Emergency Overview

**Physical Description & Colour:** Clear dark liquid.

**Odour:** Characteristic aromatic odour.

**Major Health Hazards:** repeated exposure may cause skin dryness or cracking, vapours may cause drowsiness and dizziness, causes serious eye irritation.

## Section 3 - Composition/Information on Ingredients

Ingredients	CAS No	Conc,%	TWA (mg/m <sup>3</sup> )	STEL (mg/m <sup>3</sup> )
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	50-75	not set	not set
Distillates, hydrotreated, light	64742-47-8	25-50	not set	not set
Isopropanol	67-63-0	5-10	983	1230
Acetone	67-64-1	5-10	1185	2375
Methyl ethyl ketone	78-93-3	5-10	445	890
Xylene	1330-20-7	1-5	350	655
Other non-hazardous ingredients	various	to 100	not set	not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak "is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

## Section 4 - First Aid Measures

### General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

**Inhalation:** No first aid measures normally required. However, if inhalation has occurred, and irritation has developed, remove to fresh air and observe until recovered. If irritation becomes painful or persists more than about 30 minutes, seek medical advice.

**Skin Contact:** Gently blot away excess liquid. Wash gently and thoroughly with water (use non-abrasive soap if necessary) for 5 minutes or until chemical is removed.

**Eye Contact:** Quickly and gently blot material from eyes. No effects expected. If irritation does occur, flush contaminated eye(s) with lukewarm, gently flowing water for 5 minutes or until the product is removed. Obtain medical advice if irritation becomes painful or lasts more than a few minutes. Take special care if exposed person is wearing contact lenses.

**Ingestion:** If product is swallowed or gets in mouth, do NOT induce vomiting; wash mouth with water and give some water to drink. If symptoms develop, or if in doubt contact a Poisons Information Centre or a doctor.

## Section 5 - Fire Fighting Measures

**Fire and Explosion Hazards:** The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both), fire gases. There is a moderate risk of an explosion from this product if commercial quantities are involved in a fire. Firefighters should take care and appropriate precautions. Any explosion will likely spread the fire to surrounding materials. Water spray may be used to cool drums involved in a fire, reducing the chances of an explosion. Violent steam generation or eruption may occur upon application of direct water stream on hot liquids. Vapours from this product are heavier than air and may accumulate in sumps, pits and other low-lying spaces, forming potentially explosive mixtures. They may also flash back considerable distances.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

**Extinguishing Media:** Try to contain spills, minimise spillage entering drains or water courses.

**Fire Fighting:** If a significant quantity of this product is involved in a fire, call the fire brigade. There is a danger of a violent reaction or explosion if significant quantities of this product are involved in a fire. Recommended personal protective equipment is full fire kit and breathing apparatus.

**Flash point:** 4°C, TCC

**Upper Flammability Limit:** No data.

**Lower Flammability Limit:** No data.

## SAFETY DATA SHEET

Issued by: Howard Products (Aust)

Phone: 1800 672 646 (business hours)

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)

**Autoignition temperature:** No data.  
**Flammability Class:** Flammable Category 2 (GHS); Highly Flammable (AS1940).

## Section 6 - Accidental Release Measures

**Accidental release:** This product is sold in small packages, and the accidental release from one of these is not usually a cause for concern. For minor spills, clean up, rinsing to sewer and put empty container in garbage. Although no special protective clothing is normally necessary because of occasional minor contact with this product, it is good practice to wear impermeable gloves when handling chemical products. In the event of a major spill, prevent spillage from entering drains or water courses and call emergency services.

## Section 7 - Handling and Storage

**Handling:** Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

**Storage:** Store in a cool, well ventilated area, and make sure that surrounding electrical devices and switches are suitable. Check containers periodically for leaks. Containers should be kept closed in order to minimise contamination and possible evaporation. Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. If you keep more than 2500kg or L of Dangerous Goods of Packaging Group II, you may be required to license the premises or notify your Dangerous Goods authority. If you have any doubts, we suggest you contact your Dangerous Goods authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

## Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

<b>SWA Exposure Limits</b>	<b>TWA (mg/m<sup>3</sup>)</b>	<b>STEL (mg/m<sup>3</sup>)</b>
Isopropanol	983	1230
Acetone	1185	2375
Methyl ethyl ketone	445	890
Xylene	350	655

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

**Ventilation:** This product should only be used in a well ventilated area. If natural ventilation is inadequate, use of a fan is suggested.

**Eye Protection:** Eye protection such as protective glasses or goggles is recommended when this product is being used.

**Skin Protection:** You should avoid contact even with mild skin irritants. Therefore you should wear suitable impervious elbow-length gloves and facial protection when handling this product. See below for suitable material types.

**Protective Material Types:** We suggest that protective clothing be made from the following materials: rubber.

**Respirator:** Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above. Otherwise, not normally necessary.

Safety deluge showers should, if practical, be provided near to where this product is being handled commercially.

## Section 9 - Physical and Chemical Properties:

**Physical Description & colour:** Clear dark liquid.  
**Odour:** Characteristic aromatic odour.  
**Boiling Point:** >93°C at 100kPa  
**Freezing/Melting Point:** No specific data. Liquid at normal temperatures.  
**Volatiles:** No data.  
**Vapour Pressure:** 6.8 kPa at 20°C  
**Vapour Density:** >1  
**Specific Gravity:** 0.87  
**Water Solubility:** Insoluble.  
**pH:** No data.

## SAFETY DATA SHEET



## Potential Health Effects

### Inhalation:

**Short Term Exposure:** High vapour pressures may cause drowsiness and dizziness. In addition product may be mildly irritating, although unlikely to cause anything more than mild transient discomfort.

**Long Term Exposure:** Vapours may cause drowsiness and dizziness.

### Skin Contact:

**Short Term Exposure:** Available data indicates that this product is not harmful. It should present no hazards in normal use. However product may be irritating, but is unlikely to cause anything more than mild transient discomfort.

**Long Term Exposure:** Repeated exposure may cause skin dryness or cracking.

### Eye Contact:

**Short Term Exposure:** This product causes serious eye irritation, symptoms are expected to gradually disappear once product is removed if exposure is brief, but prolonged exposure may result in long-term or permanent effects.

**Long Term Exposure:** No data for health effects associated with long term eye exposure.

### Ingestion:

**Short Term Exposure:** Significant oral exposure is considered to be unlikely. This product, while believed to be not harmful, is likely to cause headache and gastric disturbance such as nausea and vomiting if ingested in significant quantities. However, this product may be irritating to mucous membranes but is unlikely to cause anything more than transient discomfort.

**Long Term Exposure:** No data for health effects associated with long term ingestion.

### Carcinogen Status:

**SWA:** No significant ingredient is classified as carcinogenic by SWA.

**NTP:** No significant ingredient is classified as carcinogenic by NTP.

**IARC:** Isopropanol is Class 3 - unclassifiable as to carcinogenicity to humans.

See the IARC website for further details. A web address has not been provided as addresses frequently change.

## Section 12 - Ecological Information

Ecotoxicity data are available for ingredients when tested against Algae, Fish, Daphnia and Bacteria. They indicate that this product is not toxic to aquatic organisms.

However there is no data available for biodegradability, bioaccumulation, mobility or chemical fate. The product is believed to be biodegradable but not *readily* biodegradable.

Avoid discharge of this product to waterways.

## Section 13 - Disposal Considerations

**Disposal:** Dispose of small quantities and empty containers by wrapping with paper and putting in garbage. For larger quantities, if recycling or reclaiming is not possible, use a commercial waste disposal service.

## Section 14 - Transport Information

**UN Number:** 1263, PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound) (see 3.2.5 for relevant AUST entries)

**Hazchem Code:** •3YE

**Special Provisions:** 163

**Limited quantities:** ADG 7 specifies a Limited Quantity value of 5 L for this class of product.

**Dangerous Goods Class:** Class 3: Flammable liquids.

**Packing Group:** II

**Packing Instruction:** P001, IBC02

Class 3 Flammable Liquids shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 2.1 (Flammable Gases where flammable liquids and flammable gases are both in bulk), 2.3 (Toxic Gases), 4.2 (Spontaneously Combustible Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), 6 (Toxic Substances, except Flammable Liquid is nitromethane), and 7 (Radioactive Substances). They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.1 (Flammable Gases except where the Flammable Liquids and Flammable Gases are in bulk), 2.2 (Non-Flammable Non-Toxic Gases), 4.1 (Flammable Solids), 4.3 (Dangerous When Wet Substances), 6 (Toxic Substances, where Flammable Liquid is nitromethane), 8 (Corrosive Substances), 9 (Miscellaneous Dangerous Goods), Foodstuffs or foodstuff empties.

## SAFETY DATA SHEET

## Section 15 - Regulatory Information

**AICS:** All of the significant ingredients in this formulation are compliant with NICNAS regulations. The following ingredients: Distillates (petroleum), hydrotreated heavy paraffinic (a liquid hydrocarbon), Acetone, Methyl ethyl ketone, are mentioned in the SUSMP.

## Section 16 - Other Information

**This SDS contains only safety-related information. For other data see product literature.**

### Acronyms:

<b>ADG Code</b>	Australian Code for the Transport of Dangerous Goods by Road and Rail (7 <sup>th</sup> edition)
<b>AICS</b>	Australian Inventory of Chemical Substances
<b>SWA</b>	Safe Work Australia, formerly ASCC and NOHSC
<b>CAS number</b>	Chemical Abstracts Service Registry Number
<b>Hazchem Code</b>	Emergency action code of numbers and letters that provide information to emergency services especially firefighters
<b>IARC</b>	International Agency for Research on Cancer
<b>NOS</b>	Not otherwise specified
<b>NTP</b>	National Toxicology Program (USA)
<b>R-Phrase</b>	Risk Phrase
<b>SUSMP</b>	Standard for the Uniform Scheduling of Medicines & Poisons
<b>UN Number</b>	United Nations Number

THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS. OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This SDS is prepared in accord with the SWA document "Preparation of Safety Data Sheets for Hazardous Chemicals – Code of Practice" (Feb 2016)

Copyright © Kilford & Kilford Pty Ltd, June, 2021.

<http://www.kilford.com.au/> Phone (02)8321 8866

## SAFETY DATA SHEET